

E695HT

POWERED BY



YAMAHA

PERFORMANCE BULLETIN



TEST PERFORMANCE SUMMARY

RPM	Ave km/h	Ave L/h	Ave km/L
1000	9.90	5.30	1.90
1500	12.00	8.50	1.40
2000	15.00	14.40	1.00
2500	19.80	20.10	1.00
3000	27.50	23.70	1.20
3500	44.40	32.30	1.40
4000	51.90	43.00	1.20
4500	60.30	57.00	1.10
5000	67.20	71.60	0.90
5500	73.50	93.40	0.80
5700	77.30	95.20	0.80

Max. Average Speed	77.3Km/h or 41.74 knots
Best Cruising Km/L	1.40 Km/L @ 3500RPM
Range based on 95% Fuel Capacity at Best Km/L	465.5 Kilomteres

Data may vary due to changes in weather, tides, boat load, hull & propeller conditions, temperature, atmospheric pressure and wind direction.
Fuel data gathered with a non-calibrated Yamaha fuel gauge.

Speed data recorded with GPS receiver.

Yamaha Motor Australia accepts no responsibility for the accuracy of these readings.
All test data is recorded with the engine fully trimmed in (-4), until 5500 RPM, where possible.
*Range is calculated on the largest tank possible for the particular model.



F250
XCB2

PROP SPECIFICATIONS

Series	Saltwater II SDS
Diameter / Pitch	15 ^{1/2} x 17"
Part Number	6CE-45978-00

ENGINE SPECIFICATIONS

Displacement	4169cc
Engine Type	24-Valve DOHC, 4.2L V6
Weight	294kg
Gear Ratio	1.75:1 (21/12)
Mounting Height	3rd Hole